



TECHNICAL DATA	AP8	AP10	AP12	AP15
Transducers	1 x 8" / 1 x 1"	1 x 10" / 1 x 1"	1 x 12" / 1 x 1"	1 x 15" / 1 x 1"
Coverage	80 x 60°	90 x 40° Rotating	90 x 40° Rotating	90 x 40° Rotating
Nominal Impedance	LF & HF 8	LF & HF 8	LF & HF 8	LF & HF 8
Power AES	250 W	300 W	500 W	600 W
Maximum Peak SPL	119 dB SPL	120 dB SPL	126 dB SPL	127 dB SPL
Dimensions (WxHxD)	232 X 407 X 270 mm.	286 X 530 X 337 mm.	338 X 587 X 364 mm.	415 X 648 X 401 mm.
Frequency Range	65 Hz a 18 kHz	50 Hz a 18 kHz	45 Hz a 18 kHz	40 Hz a 18 kHz
Sensitivity (1 W/ 1m)	1 w @ 1 m: 94 dB	1 w @ 1 m: 96 dB	1 w @ 1 m: 97 dB	1 w @ 1 m: 98 dB
Weight	11 Kg	16 Kg	26 Kg	30 Kg
Enclosure Geometry	Elliptical trapezoidal	Elliptical trapezoidal	Elliptical trapezoidal	Elliptical trapezoidal
Angle adjustment				
Enclosure Material	Birch Plywood 15 mm.	Birch Plywood 15 mm.	Birch Plywood 15 mm.	Birch Plywood 18 mm.
Riggings	M8	M8	M8	M8
Connectors	2 x Speakon NL2 Neutrick	2 x Speakon NL2 Neutrick	2 x Speakon NL2 Neutrick	2 x Speakon NL2 Neutrick
Finish	High Strength component resin. Black	High Strength component resin. Black	High Strength component resin. Black	High Strength component resin. Black