

# INFORMACIÓN TÉCNICA

## TECHNICAL INFORMATION



Model	Altea-415A	Altea-412A
Power Amplifier	800 W <sub>peak</sub> -400 W <sub>continuous</sub> Class D Bi amplified	800 W <sub>peak</sub> -400 W <sub>continuous</sub> Class D-Bi-amplified
Input Type	Balanced	Balanced
Input Impedance	Line 20 kohms	Line 20 kohms
Sensitivity	Line: 1.95 V (+8 dBu)	Line: 1.95 V (+8 dBu)
Frequency Range	50 Hz - 20 kHz	60 Hz - 20 kHz
Rated Maximum Peak SPL	128 dB	126 dB
HF Horn Coverage Angles	90° x 60°	90° x 60°
Enclosure Material	Polypropylene	Polypropylene
Color/Finish	Black/Textured	Black/Textured
Transducers/Replacement Parts	LF: 15Mi4/GM-15Mi4 HF: M-32/GM-M-32	LF: 12Mi4/GM-12Mi4 HF: M-32/GM-M-32
Connectors	INPUT: Female XLR AUX INPUT: 1/8" (3.5 mm) Mini Jack LOOP THRU: Male XLR AC INPUT: Male IEC	INPUT: Female XLR AUX INPUT: 1/8" (3.5 mm) Mini Jack LOOP THRU: Male XLR AC INPUT: Male IEC
AC Power Requirements	2.4 A, 115 V, 50/60 Hz 1.2 A, 230 V, 50/60 Hz	2.4 A, 115 V, 50/60 Hz 1.2 A, 230 V, 50/60 Hz
Dimensions	710 x 440 x 380 mm 28 x 17.3 x 15 in	650 x 380 x 346 mm 25.59 x 14.96 x 13.62 in
Weight	19.3 kg (42.4 lb)	17.9 kg (38.7 lb)
Accessories	ANL-1 TRD-2 TRD-6 FUN-ALT15	ANL-1 TRD-2 TRD-6 FUN-ALT12

Model	Altea-415	Altea-412
Peak Power Handling	1400 W	1200 W
RMS Power Handling	350 W	300 W
Frequency Range	63 Hz - 20 kHz	68 Hz - 20 kHz
Nominal Impedance	8 ohms	8 ohms
On Axis Sensitivity	96 dB SPL	96 dB SPL
Maximum Peak SPL	128 dB	127 dB
HF Horn Coverage Angles	90° x 60°	90° x 60°
Enclosure Material	Polypropylene	Polypropylene
Color/Finish	Black/Textured	Black/Textured
Transducers/Replacement Parts	LF: 15Mi/GM-15Mi HF: M-32/GM-M-32	LF: 12Mi/GM-12Mi HF: M-32/GM-M-32
Connectors	2 x NL4 Speakon	2 x NL4 Speakon
Dimensions	710 x 440 x 380 mm 28 x 17.3 x 15 in	650 x 380 x 346 mm 25.59 x 14.96 x 13.62 in
Weight	17.5 kg (38.1lb)	16.4 kg (16.1 lb)
Accessories	ANL-1 TRD-2 TRD-6 FUN-ALT15	ANL-1 TRD-2 TRD-6 FUN-ALT12