

CABINETS/ Verso Series

Self-powered Portable Cabinets



APPLICATIONS

- Sound for events and audiovisual presentations
- Sound reinforcement
- Stage monitors
- Clubs, discos and leisure centres
- Mobile discos and shows

ACCESSORIES



VERS08 / VERS08P:

- SR8 / SR12 / TRIP01

VERS012P:

- SR12 / TRIP01

VERS0SB115P:

- POLE01

Its external cosmetic design, modern and balanced, has been created with the collaboration of the reputed team **Giugiaro Design**.



VERS08 / 8P

VERS08 Connection Plate

VERS012P

VERS012P Connection Plate

VERS0 SB115P VERS0 SB115P Connection Plate

KEY FEATURES

VERS08P / VERS012P:

- Full range, 2-way, self-powered loudspeaker
- Active crossover with 24 dB/oct slope
- Two MICRO/LINE XLR inputs with sensitivity switch
- • Two-way mixer
- 3-band tone control at mixer output
- Balanced "STACK OUT" output for connection to other units or amplifiers
- Effective protection system to reduce signal clipping
- Carry handle at the rear
- 6 flying points
- Prepared for landscape installation on the ground, with no need for accessories
- Protective grill at the front, acoustically transparent
- 35 mm stand at the base for pole mount
- EASE Win file available

VERS08:

- Passive version of VERS08P loudspeaker

VERS0SB115P:

- 15" woofer
- 500 WRMS integrated amplifier
- XLR inputs with mono conversion
- XLR stack outputs (link to other SB115P units, VERSO P speakers, etc.)
- PHASE and volume controls
- Internal 100 or 150 Hz LPF (selectable)
- Top-hat 35 mm. standard pole mount socket

	VERS08	VERS08P	VERS012P	VERS0SB115
RMS power / Program power	150W / 300W	200W / 400W	450W / 900W	500W / 1000W
Woofer / driver	8" / 1"	8" / 1"	12" / 1,75"	15" / -
Inputs / Outputs	-	2 MIC/LINE	2 MIC/LINE	1 ST LINE (mono conversion) / Stack out
Max SPL @ 1m	119 dB	118 dB	123 dB	125 dB
Dimensions / Weight	HxWxD: 398x291x241mm / 8,0 kg.	HxWxD: 398x291x241mm / 11,0 kg.	HxWxD: 475x350x290mm / 12,5 kg.	HxWxD: 450x590x490mm / 41,3 kg.