

Name	Meridian Mobile SP225
Colour	grey
Properties	OFC oxygen free copper
Properties	Analog
Application area	Studio / Broadcast
Application area	Mobile outdoor / indoor
Application area	Stage / live
Application area	ELA 100 V
Colour detailed	dark grey
Construction	(2LIY2,5mm ²)Y
Construction (audio)	(2LIY2,5mm ²)Y
Jacket material	PVC
Jacket material (audio)	PVC
Jacket Ø [mm]	7,80
Jacket Ø (audio) [mm]	7,80
Number of Channels (audio)	1
Inner conductor (audio)	2
Inner conductor (audio) [mm²]	2,50
Inner conductor Ø (audio) [mm]	1,78
AWG (audio)	13
Copper strands (audio)	140
Packing	500 m spool
Packing	100 m spool
Style variant	round
Application	Speaker Cable
Copper strand Ø (audio) [mm]	0,15
Conductor insulation Ø [mm]	3,05
Conductor insulation Ø (audio) [mm]	3,05
Width [mm]	7,8
Height [mm]	7,8
Temperature min. [°C]	-30
Temperature max. [°C]	70
Weight per 1 m [g]	106
Fire load per m [kWh]	0,33
Insulation resist. per 1 km [GΩ]	0,005
Leakage resistance at 1 km (audio) [GΩ]	0,005
Cond. resistance per 1 km [Ω]	7,5
Conductor resistance at 1 km (audio) [Ω]	7,5
Capac. cond./cond. per 1 m (audio) [pF]	136