

| | |
|---|----------------------------|
| Name | Meridian Mobile SP240 |
| Colour | grey |
| Properties | OFC oxygen free copper |
| Properties | Analog |
| Application area | Studio / Broadcast |
| Application area | Mobile outdoor / indoor |
| Application area | Stage / live |
| Application area | ELA 100 V |
| Colour detailed | dark grey |
| Construction | (2LIY4,0mm ²)Y |
| Construction (audio) | (2LIY4,0mm ²)Y |
| Jacket material | PVC |
| Jacket material (audio) | PVC |
| Jacket Ø [mm] | 9,50 |
| Jacket Ø (audio) [mm] | 9,50 |
| Number of Channels (audio) | 1 |
| Inner conductor (audio) | 2 |
| Inner conductor (audio) [mm²] | 4,00 |
| Inner conductor Ø (audio) [mm] | 2,76 |
| AWG (audio) | 11 |
| Copper strands (audio) | 56 |
| Packing | 500 m spool |
| Packing | 100 m spool |
| Style variant | round |
| Application | Speaker Cable |
| Copper strand Ø (audio) [mm] | 0,30 |
| Conductor insulation Ø [mm] | 4,20 |
| Conductor insulation Ø (audio) [mm] | 4,20 |
| Width [mm] | 9,5 |
| Height [mm] | 9,5 |
| Temperature min. [°C] | -30 |
| Temperature max. [°C] | 70 |
| Weight per 1 m [g] | 150 |
| Fire load per m [kWh] | 0,46 |
| Insulation resist. per 1 km [GΩ] | 0,005 |
| Leakage resistance at 1 km (audio) [GΩ] | 0,005 |
| Cond. resistance per 1 km [Ω] | 4,5 |
| Conductor resistance at 1 km (audio) [Ω] | 4,5 |
| Capac. cond./cond. per 1 m (audio) [pF] | 125 |