



LOUDSPEAKERS/

CABINET LOUDSPEAKERS/

eAMBIT106

Applications

- Shopping centres
- Retail shops
- PA distributed sound systems
- Clubs, Cafes, Bars foreground/
background reinforcement
- Health and sports centres
- Meeting and conference rooms

Loudspeaker cabinet

eAMBIT106 is an ultra compact 2 way coaxial loudspeaker cabinet with neutral and discreet design. It mounts a 6.5" woofer and 1" tweeter. Especially suitable for background music reinforcement in retail shops, restaurants, cafés, corporate premises and education rooms.



Key Features

- ABS 2-way, 50 WRMS architectural
- 6,5" woofer / 1" tweeter
- Built-in audio transformer for 100V applications
- 8 ohms and 70/100V operation selector
- Includes on-wall hardware, safety sling, screws and wrench for fast installation
- Available in black and white colours
- Spring loaded input terminals
- IP54 rated
- Anti UV cabinet avoids colour degradation in case of direct sunlight exposition



Main Technical Specifications	Nominal low impedance	8Ω			
	RMS power	50 W			
	Nominal high impedance	70/100V Line			
	Power selector @ 100V	5, 7.5, 15, 30 W			
	Sensitivity 1W/1m	93 dB			
	Frequency response (-3 dB)	110Hz – 20kHz			
	Dimensions (without accessories) / weight	H: 210 mm	L: 210 mm	W: 160 mm	2.75 Kg

Accessories

- MP106AMB2/WH, MP106AMB3/WH, MP106AMB4/WH: for 2,3 or 4 units cluster configuration
- SR6/WH: on wall bracket for MP106AMB2 cluster



SR6 ON WALL



MP106AMB3/WH