



# LOUDSPEAKERS/

## CABINET LOUDSPEAKERS/

### eAMBIT103

#### Applications

- Shopping centres
- Retail shops
- PA distributed sound systems
- Clubs, Cafes, Bars foreground/  
background reinforcement
- Health and sports centres
- Meeting and conference rooms

## Loudspeaker cabinet

eAMBIT103 is an ultra compact 2 way coaxial loudspeaker cabinet with neutral and discreet design. It mounts a 3.5" woofer and 0.5" tweeter. Especially suitable for background music reinforcement in retail shops, restaurants, cafés, corporate premises and education rooms.



#### Key Features

- ABS 2-way, 25 WRMS architectural loudspeaker
- 3,5" woofer / 0,5" tweeter
- Built-in audio transformer for 100V applications
- 8 ohms and 70/100V operation selector
- Includes on-wall hardware, safety sling, screws and wrench for fast installation
- Available in black and white colours
- Spring loaded input terminals
- IP54 rated
- Anti UV cabinet avoids colour degradation in case of direct sunlight exposition



Main Technical Specifications	Nominal low impedance	8Ω			
	RMS power	25W			
	Nominal high impedance	70/100V Line			
	Power selector @ 100V	2.5, 5, 7.5, 15 W			
	Sensitivity 1W/1m	87 dB			
	Frequency response (-3 dB)	150Hz – 20kHz			
	Dimensions (without accessories) / weight	H: 120 mm	L: 120 mm	W: 117 mm	1.275 Kg

#### Accessories

- MP103AMB2, MP103AMB4 for 2 or 4 units cluster configuration



MP103AMB2